

Thank you for purchasing the AM-2509 “heavy-duty” tripod antenna stand. Please read these instructions carefully before setting up.

SPECIFICATIONS

Weight: 9.5 lbs

Collapsed Height: 54 in.

Extended Height: 96 in.

Maximum Load: 100 lbs

Mast Material: 1.4 in. OD Steel

Mast Locking: Through-bolt (locking key)

Tripod Area: 4.8-ft²

SETUP

- To open up tripod legs, loosen the locking knob and press down on the leg assembly.
- Set the desired spread and tighten the locking knob.
- If not already installed, insert extension tube in the tripod base and lock it in place.

INSTALLATION TIPS

The AM-2509 is designed for temporary outdoor applications only, so avoid prolonged exposure to the elements. When setting up, choose a hard level surface such as pavement, firmly packed gravel, concrete, etc. When attaching antennas or other items, center the load over the radius area of the legs to prevent tilting. A carpenter’s level will confirm if the mast is leaning or centered. Top heavy loads can be dangerous, so do not hesitate to reduce mast height if the load is not well balanced or presents a large wind-loading area.

Important Note: The best way to prevent damage to property or injury to bystanders is to install guy lines. Even with careful setup, a sudden gust of wind or an inadvertent tug on the mast could easily topple an un-guyed load. Guying supplies are available from Intellitron and its distributors.

Important Warning: Never assemble or install the AM-2509 where the mast could contact power lines or building-entrance cables. Also, avoid setting up in areas where bystanders could be injured, or valuable property damaged by a mast failure.



TWO YEAR LIMITED WARRANTY

This Limited Product Warranty is provided by the Dealer where your Intellitron product was purchased. The Product Warranty extends only to the original purchaser of the product and is valid for a period of two years from the date of purchase. Please keep your dated sales receipt as evidence of the date of purchase. You will need it to receive warranty service. Your Dealer warrants the product will be free from defects in workmanship and materials under normal use. If the product fails to conform to the warrant and is within the warranty period of two years, contact your original dealer for a return authorization. Your dealer may choose to either repair or replace the non-conforming product.